



WRIST STRAP COIL CORDS

Features :

Cord : Antistatic Nylon, PE shrink tube
Alligator clip : Chromed steel
Banana plug : Stainless brass
Female stud : Stainless brass

Electrical properties :

Resistance : 1 M Ω

Compliance to standards :

IEC 61340-5-1
RoHS Directive (2002/95/CE)

Features & part-numbers :

Connections	Length	References
4mm / banana	1.8m	30-560-0604
4mm / banana	3.0m	30-560-1004
7mm / banana	1.8m	30-560-0607
7mm / banana	3.0m	30-560-1007
10mm / banana	1.8m	30-560-0610
10mm / banana	3.0m	30-560-1010
4mm / 10mm stud	1.8m	30-560-0641
7mm / 7mm stud	1.8m	30-560-0677
10mm / 10mm stud	1.8m	30-560-0611
7mm / 10mm stud	1.8m	30-560-0671
4mm / GSGS	1.8m	30-560-0614
4mm / GSGS	3.0m	30-560-1014
4mm / 4.5mm stud	1.8m	30-560-0645

Options :

Other length, other connections available on request.



CORDONS TORSADES

Propriétés :

Cordons : Nylon antistatique, PE retractible
Pince crocodile : Acier chromé
Fiche banane : Cuivre inoxydable
Pression femelle : Cuivre inoxydable

Propriétés électriques :

Résistance : 1 M Ω

Conformité aux normes :

IEC 61340-5-1
Directive RoHS (2002/95/CE)

Connections, Longueur et Référence :

Connections	Longueur	Références
4mm / banane	1.8m	30-560-0604
4mm / banane	3.0m	30-560-1004
7mm / banane	1.8m	30-560-0607
7mm / banane	3.0m	30-560-1007
10mm / banane	1.8m	30-560-0610
10mm / banane	3.0m	30-560-1010
Pressions 4mm / 10mm	1.8m	30-560-0641
Pressions 7mm / 7mm	1.8m	30-560-0677
Pressions 10mm / 10mm	1.8m	30-560-0611
Pressions 7mm / 10mm	1.8m	30-560-0671
4mm / GSGS	1.8m	30-560-0614
4mm / GSGS	3.0m	30-560-1014
4mm / 4.5mm stud	1.8m	30-560-0645

Options :

Autres longueur, autres connections disponibles sur demande.